

STARK PERMAFLEX SLF 200 is a two part, 100% solids urethane compounded for the repair of rubber, PVC conveyor belts and linings.

STARK Permafex 60SLF is available in 200ml x 200ml and 750ml x 750ml sizes. The 200ml x 200ml is perfect for small repairs and is dispensed using a light weight manually operated dispenser. The STARK 750ml x 750ml Cartridge is the largest dual cartridge available. There is a total of 1590g (3.5lbs) of material in one 750ml x 750ml cartridge.

This cartridge is dispensed using the pneumatic dispenser. The dispenser is complete with an air manifold for the material flow control.



Permafex 750 X 750ml



Permafex 200 X 200ml

FEATURES AND BENEFITS:

- The material cures to touch in 1 minute and can be buffed after 1 hour at ambient temperature.
- 100% solids and no VOC's, making it safe to use.
- Standard system is self leveling and applied with a dual plunger dispensing gun.
- Long shelf life, 2 years when unopened. 90 days after partial use.
- PERMAFLEX will not harden over time or delaminate
- Maximum hardness of 60 +/- Shore "A".
- The unique properties of PERMAFLEX SLF ensure a long-lasting permanent bond and flexible repair, when used together with PF-84 primer.

PROPERTIES

- COLOR: Black
- ELASTOMER: POLYURETHANE
- ELONGATION AT BREAK: 525 %
- ABRASION RESISTANCE: 195 mm³
- TENSILE STRENGTH: 1550 PSI